



Suction Feed Low Pressure Spraygun

D.I.Y

Feed type: Pressure
Standard nozzle: 1.3mm
Optional nozzle: 1.2mm
Average air consumption:
3CFM / 85L/min
Cup Capacity: 0.8L
Recommended Air
Pressure: 10 -40Psi
Canister Capacity: 0.8L
Paint Nozzle: 1.3mm
TOOS1784



Suction Feed High Pressure Spray Gun

Industrial

Standard Nozzle: 1.6mm
Cup Capacity: 1L
Avg Air Consumption:
10CFM / 280L/min
Recommended Air Pressure:
355 - 480kPA/ 3.5 - 4.8 bar
Canister Capacity: 0.8L
Adjustable spray pattern
Non-bleeder type, siphon feed
External mix nozzle
Dual Action trigger
Air inlet 1/4" BSP
Paint nozzle: 2.0mmØ
Professional quality
Min recommended compressor:
2HP/ 1.5KW and above
TOOS1785



Air Duster

Semi-Industrial

Short nozzle

Maximum pressure: 9 bar
Min compressor required: 1.1KW
Pressure required: 3 - 8 bar
Suitable for blowing and
cleaning away cuttings etc
TOOS1751



Blow Gun

Semi-Industrial

Extended nozzle

Air inlet: 6.5mm
Suitable for unblocking oilways
in engines & machine parts,
cleaning electrical circuit boards
& computers, general cleaning
duties in & around the workshop
PAB1208